

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Glass Fibre Products**

with type designation(s)

**Tri-axial; Y-E (300-3000 g/m²) and K-E (300-3000 g/m²) with or without S (3-1000 g/m²),
Tri-axial; Y-E (300-3000 g/m²) and K-E (300-3000 g/m²) with or without V (3-1000 g/m²),
- with or without stabilization (1-500 g/m²)**

Issued to

**Devold AMT AS
LANGEVÅG, Norway**

is found to comply with

**DNV GL class programme DNVGL-CP-0467 – Type approval – Uni- and multi-axial multi-ply
fabrics made of glass fibres****DNV GL rules for classification – High speed and light craft****DNV GL standard DNVGL-ST-0342 – Craft****Det Norske Veritas' Standards for Certification No. 2.20, Lifeboats and Rescue Boats, 2007****Application :****For use in marine vessels in accordance with stated Rules/Standards.****Product(s) approved by this certificate is/are accepted for installation on all vessels classed
by DNV GL.**This Certificate is valid until **2021-12-18**.Issued at **Høvik** on **2016-12-19**DNV GL local station: **Ålesund**Approval Engineer: **Gisle Hersvik**for **DNV GL**

**Martin Strande
Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Product description

Tri-axial; Y-E (300-3000 g/m²) and K-E (300-3000 g/m²) with or without S (3-1000 g/m²)
Tri-axial; Y-E (300-3000 g/m²) and K-E (300-3000 g/m²) with or without V (3-1000 g/m²)
- with or without stabilization (1-500 g/m²)

Tri-axial Glass Fiber products, of 0°/+45°/-45° orientation:

Y-E and CSM/CFM reinforced Y-S-E (S3 to S1000) or Y-E and V reinforced Y-V-E (V3 to V1000)

Tri-axial Glass Fiber products, of +45°/90°/-45° orientation:

K-E and CSM/CFM reinforced K-S-E (S3 to S1000) or K-E and V reinforced K-V-E (V3 to V1000)

Legends:

CSM	Chopped strand mat
CFM	Chopped fiber mat
V	Fleece
S	CSM/CFM
E	Glass
Y	Triax 0°/+/-
K	Triax -/90°/+

Manufactured by

Devold AMT UAB, Pramonės g. 20D, 81123 Kursenai, Lithuania

DNV GL local office: Klaipėda

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Type Approval documentation

1. Previous Type Approval Certificate No. K-6127.
2. Email from DNV GL Klaipėda of 2016-12-09, incl. Assessment Report of 2016-12-09.
3. Email from DNV GL Ålesund of 2016-12-09, incl. Assessment Report of 2016-12-09.
4. Email from Devold AMT AS of 2016-12-01, incl. changes to product naming and Application for Type Approval of 2016-12-01.
5. Email from DNV GL Klaipėda of 2014-09-18, incl. Periodical Assessment Report from DNV GL Klaipėda of 2014-05-07 and letter from Devold AMT UAB re. Change of company name.
6. Various correspondences between DNV GL and Devold AMT AS, December 2013-September 2014.
7. Email from DNV Klaipėda of 2012-06-20, incl. Application for Type Approval of 2012-05-03, Asbestos declaration of 2012-05-03 and Survey Report of 2012-06-20.
8. Letter from Devold AMT AS of 2011-11-16, and Application for Type Approval of 2011-11-16.
9. Letter from DNV Ålesund of 2008-05-16 and Survey Report of 2008-05-07.
10. Devold's Product Specifications and similar certificate issued to Devold AMT AS, Norway.

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**.

Marking of product

Product shall be marked with *manufacturer's name*; **Devold AMT AS**, *place of production* and *type designation*.

Job Id: **262.1-018263-9**
Certificate No: **TAK00000M1**

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and DNV GL Type Approval Certificate.

END OF CERTIFICATE